



轴承型号 Bearing No	外形尺寸 Dimension(mm)					额定载荷 (N)		重量 Weight (Kg)
	d	D	B	B1	r (min)	Cr	Cor	
R 144	3.175	6.35	2.38	2.779	0.08	294	98	0.0003
R 2	3.175	9.525	3.969	3.969	0.30	640	226	0.0014
R 2A	3.175	12.7	4.366	4.366	0.30	640	226	0.0033
EE0	3.175	12.7	4.366	4.366	0.30	715	283	0.0033
R 155	3.969	7.938	2.779	3.175	0.08	392	147	0.0006
R 156	4.762	7.938	2.779	3.175	0.08	392	147	0.0005
R 166	4.762	9.525	3.175	3.175	0.08	715	274	0.0008
R 186	4.762	12.7	2.779	3.969	0.13	1313	490	0.0020
R 3	4.762	12.7	3.969	4.978	0.30	1310	485	0.0029
EE1	4.762	12.7	3.969	4.978	0.30	1310	485	0.0029
1601	4.762	17.462	6.35	7.938	0.30	1970	730	0.0070
R 168	6.35	9.525	3.175	3.175	0.08	421	205	0.0006
R 188	6.35	12.7	3.175	4.762	0.13	833	372	0.0020
R 4	6.35	15.875	4.978	4.978	0.30	1470	600	0.0045
1602	6.35	17.4652	6.35	7.938	0.30	1970	730	0.0065
R 4A	6.35	19.05	5.556	7.144	0.40	2410	911	0.0100
EE 2	6.35	19.05	50556	70144	0.40	2410	911	0.0100
R 1810	7.938	12.7	3.969	3.969	0.13	882	421	0.0017
1603	7.938	22.225	7.144	8.731	0.30	3290	1360	0.0120
1605	7.938	23.019	7.938	7.938	0.30	3330	1410	0.0160
R 6	9.525	22.225	5.556	7.144	0.40	3350	1410	0.0117
EE 3	9.525	22.225	5.556	7.144	0.40	3350	1410	0.0177

1604	9.525	22.225	7.144	8.731	0.40	3330	1410	0.0105
1606	9.525	23.019	7.938	7.938	0.40	3330	1410	0.0150
1614	9.525	28.575	9.525	9.525	0.60	5110	2390	0.0300
1607	11.12	23.019	7.938	7.938	0.40	2690	1270	0.0300
1615	11.12	28.575	9.525	9.525	0.60	5110	2390	0.0280
1620	11.12	34.925	11.112	11.112	0.60	7450	3700	0.0500
R 8	12.7	28.575	6.35	7.938	0.40	5110	2380	0.0210
EE 4	12.7	28.575	6.35	7.938	0.40	5110	2380	0.0210
1616	12.7	28.575	9.525	9.525	0.60	5110	2390	0.0260
RLS 4	12.7	33.338	9.525	9.525	0.60	5200	3800	0.0300
1621	12.7	34.925	11.112	11.112	0.60	7450	3700	0.0480
RMS 4	12.7	41.28	15.875	15.875	1.00	7350	4410	0.1067
1622	14.288	34.925	11.112	11.112	0.60	7450	3700	0.0460
R 10	15.875	34.925	7.144	8.731	0.80	6000	3250	0.0367
EE 5	15.875	34.925	7.144	8.731	0.80	6000	3250	0.0367
1623	15.875	34.925	11.112	11.112	0.60	7450	3700	0.0410
RLS 5	15.875	39.688	11.112	11.112	0.60	7200	4300	0.0600
1628	15.875	41.275	12.7	12.7	0.60	9390	5020	0.0720
1633	15.875	44.45	12.7	12.7	0.60	9390	5020	0.0920
RMS 5	15.875	46.04	15.875	15.875	1.00	9880	6200	0.1172
R 12	19.05	41.275	7.938	11.112	0.80	8370	4520	0.0630
EE 6	19.05	41.275	7.938	11.112	0.80	8370	4520	0.0630
1630	19.05	41.275	12.7	12.7	0.60	9390	5020	0.0690
EE 7	19.05	44.45	9.525	12.7	0.80	9390	5020	0.0900
1635	19.05	44.45	12.7	12.7	0.60	9390	5020	0.0900
RLS 6	19.05	47.625	14.288	14.288	1.00	10000	6300	0.1100
1638	19.05	50.8	14.288	14.288	0.90	10060	5860	0.1450
RMS 6	19.05	50.8	17.46	17.46	1.00	10450	6560	0.1606
R 144	22.225	47.625	9.525	12.7	0.80	10060	5920	0.0970
EE 8	22.225	47.625	9.525	12.7	0.80	10060	5920	0.0970
1640	22.225	50.8	14.288	14.288	0.90	10060	5860	0.1330
RLS 7	22.225	50.8	14.288	14.288	1.00	12000	7600	0.1300
RMS 7	22.225	57.15	17.46	17.46	1.10	10780	6980	0.2230
R 16	25.4	50.8	9.525	12.7	0.80	10060	5920	0.1070
EE 9	25.4	50.8	9.525	12.7	0.80	10060	5920	0.1070
1641	25.4	50.8	14.288	14.288	0.90	10060	5860	0.1210
RLS 8	25.4	57.15	15.875	15.875	1.00	14000	9700	0.1700
RMS 8	25.4	63.5	19.05	19.05	1.10	17220	11390	0.2590
R 18	28.575	53.975	9.525	12.7	0.80	11900	7460	0.1220
EE 10	28.575	53.975	9.525	12.7	0.80	11900	7460	0.1220
1652	28.575	63.5	15.875	15.875	0.90	19460	11310	0.2110
RLS 9	28.575	63.5	15.875	15.875	1.00	15300	10200	0.2100
RMS 9	28.575	71.44	20.64	20.64	1.10	22840	15680	0.3720
R 20	31.75	57.15	9.525	12.7	0.80	13230	8300	0.1250
EE 11	31.75	57.15	9.525	12.7	0.80	13230	8300	0.1250

1654	31.75	63.5	15.875	15.875	0.90	19460	11310	0.1930
1657	31.75	65.087	17.462	17.462	0.90	19460	11310	0.2320
R 22	34.925	63.5	11.112	14.288	0.80	16210	10420	0.1650
EE 12	34.925	63.5	11.112	14.288	0.80	16210	10420	0.1650
RLS 11	34.925	76.2	17.462	17.462	1.10	20100	13900	0.3700
RMS 11	34.925	88.9	22.23	22.23	1.50	28400	20900	0.7000
R 24	38.1	66.675	11.112	14.288	0.80	17030	11700	0.1720
EE 13	38.1	66.675	11.112	14.288	0.80	17030	11700	0.1720
RLS 12	38.1	82.55	19.05	19.05	1.10	24000	17000	0.4300
RMS 12	38.1	95.25	23.81	23.81	1.50	31390	22380	0.8000