



SHF crossed roller Bearing



Designation		Dimensions (h/li)													Basic Load ratings(KN)		Weight
Bearing	d	D	T	D1	D2	D21	D3	n1-d1	n2-d2	n21-d21	n3-d3	d31	t31	rsmin	Cr	Cor	kg
SHF14-3516A	38	70	15.1	64	64	---	44	8-φ3.5	2-M3	---	12-M3	---	5	0.5 x 45 °	5.4	7.1	0.28
SHF17-4216A	47	80	17	74	74	---	54	12-φ3.5	4-M3	---	20-M3	---	5	0.5 x 45 °	10.4	14.2	0.39
SHF20-5016A	54	90	18.5	84	84	---	62	12-φ3.5	4-M3	---	(16 + 4) -M3	---	6	0.5 x 45 °	16.1	22.4	0.5
SHF25-6218A	68	110	20.7	102	102	---	77	12-φ4.5	4-M3	---	(16-M4) + (4- M3)	---	6/8	0.5 x 45 °	17.8	27.4	0.81
SHF32-8022A	88	142	24.4	132	132	---	100	12-φ5.5	4-M4	---	(16-M5) + (4- M4)	---	8	0.5 x 45 °	25.6	42	1.7
SHF40-9524A	108	170	30	158	158	---	122	12-φ6.6	6-M4	---	(16-M6) + (4- M5)	---	8/10	0.5 x 45 °	42.1	68.4	2.79
SHF50-12031A	135	214	36	200	200	---	154	12-φ	6-M5	---	(16-M8) + (8- M5)	---	10/12	0.5 x 45 °	69.8	121.6	5.19