


Four-point Contact Ball Slewing Bearing Without Teeth



Lager Nr.	INA-Nr.	Rothe Erde Nr.	LYC-Nr.	TG-Nr.	Abmessungen (mm)				Einbaugröße (mm)				Strukturgröße (mm)						Zahnparameter (mm)				Axiale statische Nennlast (kN)	Gewicht (kg)																	
					Da	D	di	H	La	Li	n1	n2	$\phi 1$	$\phi 2$	D1	d	b	h	B	C	Di	Da			m	z	tun	x													
SR11/170					170	70	40	148	90	6	6	$\phi 9$	M8				5	35	35	121.5	118.5												4.37								
SR10/179					234	124.5	25	214	144.5	24	19	$\phi 11$	$\phi 11$						25	25	180	178											140	5.4							
SR15/179	VU 140179				234	124.5	35	214	144.5	12	12	11	11						5	30	30	178	180											220	7						
SR15/179Y					234	124.5	35	214	144.5	24	20	$\phi 11$	$\phi 11$						5	30	30	180.5	177.5												200	7					
SR20/300				E.318.22.00.D.1	300	138	46	270	170	6	6	$\phi 13.5$	$\phi 13.5$						5	41	41	220	218												350	14.34					
SR20/220	VU 200220			E.318.22.00.D.1	302	138	46	270	170	10	10	18	18						5	41	41	219	221													420	16				
SR20/220Y	VU200220			E.318.15.01.AALM	302	140	46	270	170	10	10	$\phi 18$	M16						5	41	41	223	221														435	18.5			
SR20/312					312	145.14	50	270	175	14	16	M15.88	M15.88						6	44	44	220.86	224.15														350	18.55			
SR15/200					240	160	38												5	33	33	201	199														300	6.3			
SR20/260Y					329	190	45	305	215	16	16	$\phi 14$	$\phi 14$	328	192				1	44	44	261.5	258.5															520	15.8		
SR20/257					329	190	45	305	215	16	16	$\phi 14$	$\phi 14$	328	192				1	44	44	258	256															480	16.2		
SR20/326A					326	191	46	305	215	8	8	M8	M8						5	41	41	261	259															280	16.3		
SR20/326					326	191	46	305	215	20	20	$\phi 14$	$\phi 14$						5	41	41	261	259															280	15.1		
SR20/257A					329	191	45	305	215	20	20	$\phi 14$	$\phi 14$	327	193				4	41	41	258	256															480	15		
SR20/260	VU.200.260			E.403.22.05.AALM	329	191	46	305	215	20	20	$\phi 14$	$\phi 14$		193				5	41	41	263	261															420	14.8		
SR20/260Y1	VU 200260			E.403.22.01.CC.LM	326	191	46	305	215	20	20	14	14						5	41	41	259	261															500	15		
SR20/260Y2				E.403.22.51.CC.LM	328	192	45	305	215	16	16	$\phi 14$	$\phi 14$	328	192				45	45	262	258																	540	18	
SR10/250				E.403.22.00.D1	300	200	35	280	220	16	16	M10	M10		200				5	30	30	251	249															200	7.1		
SR30/435A					435	228	78	394.5	277	8	4	42006	42006						18	60	65	335	332															830	49.6		
SR20/308					403.5	235	55	358	259	14	12	$\phi 13$	$\phi 13$	380					8	45	47	310.5	306.5																550	26.6	
SR20/341			LY-Q020	E.403.22.00.D.1	440	240	55	400	280	18	18	M20-7H	22						5	50	50	342	340																782	34.7	
SR25/345					430	260	65	400	290	24	24	$\phi 14$	$\phi 16$						12	53	53	348	342																820	32	
SR 15/325	VU 140325				380	270	35	360	290	24	24	11	11						5	30	30	324	326																460	12	
SR25/485				E.403.22.00.D.1	485	275	55	453	307	8	8	M16	M16						5	50	50	382	378																	1010	45.4
SR25/485Y					485	275	55	453	307	8	8	$\phi 18$	$\phi 18$						5	50	50	382	378																	1010	45.4
SR 25/380	VU 250380				485	275	55	453	307	16	16	18	18						5	50	50	379	381																840	45	
SR20/383			LY-Q007		485	275	55	453	307	16	16	18	M16						5	50	50	386	381																872	43.7	
SR20/383Y			LY-Q007K		485	275	55	453	307	16	16	18	18						5	50	50	386	381																872	43.7	
SR17/402				E.535.25.00.D.1	402	278	44	383	298	12	12	$\phi 9$	M8						6	38	38	342	338																470	17.3	
SR20/370		060.22.0370.301.11.1504			456	289	59	425	320	16	16	M16	M16						9	50	50	369	371																940	35	