



Medium size four-point contact ball slewing bearings with an internal gear



Bezeichnung	De(mm)	Dm(mm)	Di(mm)	Fe(mm)	he(mm)	Ne(mm)	Fi(mm)	hi(mm)	Ni(mm)	D (mm)	m(mm)	Z(mm)	Norm. Tooth(KN)	Max. Tooth force(KN)	Gewicht (kg)	Fig N°	axial dyn. C(KN)	axial stat. Co(KN)	raceways (r)	bolt (b)
RKS.062.20.0414	486	414	325	460	14	24	375	M12	24	335	5	67	18	34	31	C	169	560	1r	1b
RKS.062.20.0544	616	544	444	590	14	32	505	M12	32	456	6	76	25	45	42	C	188	740	2r	2b
RKS.062.20.0644	716	644	546	690	14	36	605	M12	36	558	6	93	25	45	50	C	200	880	3r	3b
RKS.062.20.0744	816	744	648	790	14	40	705	M12	40	660	6	110	25	45	58	C	211	1010	4r	4b
RKS.062.20.0844	916	844	736	890	14	40	805	M12	40	752	8	94	33	60	69	C	222	1150	5r	5b
RKS.062.20.0944	1016	944	840	990	14	44	905	M12	44	856	8	107	33	60	76	C	231	1280	6r	6b
RKS.062.20.1094	1166	1094	984	1140	14	48	1055	M12	48	1000	8	125	33	60	91	C	244	1490	7r	7b
RKS.062.25.1204	1289	1204	1072	1257	16	45	1151	16	45	1080	10	108	59	106	145	D	371	1943	8r	8b
RKS.062.25.1314	1399	1314	1182	1367	16	50	1261	16	50	1190	10	119	59	106	159	D	383	2124	9r	9b
RKS.062.25.1424	1509	1424	1292	1477	16	54	1371	16	54	1300	10	130	59	106	172	D	395	2304	10r	10b
RKS.062.25.1534	1619	1534	1402	1587	16	60	1481	16	60	1410	10	141	59	106	186	D	406	2485	11r	11b
RKS.062.25.1644	1752	1644	1495	1708	22	54	1580	22	54	1500	10	150	59	106	236	D	416	2666	12r	12b
RKS.062.25.1754	1862	1754	1605	1818	22	60	1690	22	60	1610	10	161	59	106	252	D	424	2847	13r	13b
RKS.062.30.1904	2012	1904	1729	1968	22	64	1840	22	64	1736	14	124	82	147	299	D	571	4048	14r	14b