



Medium size crossed cylindrical roller slewing bearings with an internal gear



Bezeichnung	De(mm)	Dm(mm)	Di(mm)	Fe(mm)	he(mm)	Ne(mm)	Fi(mm)	hi(mm)	Ni(mm)	D (mm)	m(mm)	Z(mm)	Norm. Tooth(KN)	Max. Tooth force(KN)	Gewicht (kg)	Fig N°	axial dyn. C(KN)	axial stat. Co(KN)	raceways (r)	bolt (b)
RKS.162.14.0414	484	414	325	460	14	24	375	M12	24	335	5	67	18	34	31	I	229	520	1r	1b
RKS.162.14.0544	614	544	444	590	14	32	505	M12	32	456	6	76	25	45	43	I	270	680	2r	2b
RKS.162.14.0644	714	644	546	690	14	36	605	M12	36	558	6	93	25	45	50	I	290	800	3r	3b
RKS.162.14.0744	814	744	648	790	14	40	705	M12	40	660	6	110	25	45	58	I	315	930	4r	4b
RKS.162.14.0844	914	844	736	890	14	40	805	M12	40	752	8	94	33	60	69	I	340	1050	5r	5b
RKS.162.14.0944	1014	944	840	990	14	44	905	M12	44	856	8	107	33	60	76	I	360	1170	6r	6b
RKS.162.14.1094	1164	1094	984	1140	14	48	1055	M12	48	1000	8	125	33	60	91	I	390	1360	7r	7b
RKS.162.16.1204	1289	1204	1072	1257	16	45	1151	16	45	1080	10	108	59	106	148	J	386	1836	8r	8b
RKS.162.16.1314	1399	1314	1182	1367	16	50	1261	16	50	1190	10	119	59	106	161	J	419	1995	9r	9b
RKS.162.16.1424	1509	1424	1292	1477	16	54	1371	16	54	1300	10	130	59	106	175	J	494	2352	10r	10b
RKS.162.16.1534	1619	1534	1402	1587	16	60	1481	16	60	1410	10	141	59	106	189	J	611	2912	11r	11b
RKS.162.16.1644	1752	1644	1495	1708	22	54	1580	22	54	1500	10	150	59	106	239	J	658	3133	12r	12b
RKS.162.16.1754	1862	1754	1605	1818	22	60	1690	22	60	1610	10	161	59	106	256	J	1049	3354	13r	13b
RKS.162.20.1904	2012	1904	1729	1968	22	64	1840	22	64	1736	14	124	82	147	304	J	854	4066	14r	14b