


## High Speed Double Direction Angular Contact Thrust Ball Bearing



Monton-Lager	d(mm)	D (mm)	H(mm)	Cr(KN)	Kor(KN)	Pu(KN)	Drehzahl (r/min)		Gewicht (kg)
							Fett	Öl	
BTW 35 CTN9/SP	35	62	34	16.8	39	1.83	11000	14000	0.35
BTW 40 CTN9/SP	40	68	36	19.5	46.5	2.24	10000	13000	0.42
BTW 45 CTN9/SP	45	75	38	22.1	54	2.6	9500	12000	0.53
BTW 50 CTN9/SP	50	80	38	22.5	60	2.85	9000	11000	0.58
BTW 55 CTN9/SP	55	90	44	30.2	80	3.8	7500	9000	0.87
BTM 60 ATN9/P4CDB	60	95	33	21.6	43	1.86	10100	12900	0.85
BTM 60 ATN9/HCP4CDB		95	33	21.6	43	1.86	12700	15200	0.8
BTM 60 BTN9/P4CDB		95	33	25	50	2.12	9000	11500	0.85
BTM 60 BTN9/HCP4CDB		95	33	25	50	2.12	11100	13300	0.8
BTW 60 CTN9/SP		95	44	30.7	83	4	7500	9000	0.93
BTM 65 ATN9/P4CDB	65	100	33	22	47.5	2	9500	12100	0.9
BTM 65 ATN9/HCP4CDB		100	33	22	47.5	2	11900	14200	0.85
BTM 65 BTN9/P4CDB		100	33	26	54	2.32	8400	10900	0.9
BTM 65 BTN9/HCP4CDB		100	33	26	54	2.32	10400	12400	0.85
BTW 65 CTN9/SP		100	44	31.9	90	4.3	7000	8500	1
BTM 70 ATN9/P4CDB	70	110	36	27.5	58.5	2.45	8700	11100	1.2
BTM 70 ATN9/HCP4CDB		110	36	27.5	58.5	2.45	10900	13000	1.15

## High Speed Double Direction Angular Contact Thrust Ball Bearing

BTM 70 BTN9/P4CDB		110	36	32	67	2.85	7700	9900	1.2
BTM 70 BTN9/HCP4CDB		110	36	32	67	2.85	9500	11300	1.15
BTW 70 CTN9/SP		110	48	39	112	5.3	6700	8000	1.35
BTM 75 ATN9/P4CDB	75	115	36	27.5	61	2.6	8200	10400	1.3
BTM 75 ATN9/HCP4CDB		115	36	27.5	61	2.6	10300	12300	1.2
BTM 75 BTN9/P4CDB		115	36	32.5	69.5	2.9	7300	9400	1.3
BTM 75 BTN9/HCP4CDB		115	36	32.5	69.5	2.9	9000	10700	1.2
BTW 75 CTN9/SP		115	48	39.7	116	5.6	6300	7500	1.45
BTM 80 ATN9/P4CDB	80	125	40.5	33.5	73.5	3.1	7600	9700	1.75
BTM 80 ATN9/HCP4CDB		125	40.5	33.5	73.5	3.1	9600	11500	1.65
BTM 80 BTN9/P4CDB		125	40.5	39	85	3.55	6800	8700	1.75
BTM 80 BTN9/HCP4CDB		125	40.5	39	85	3.55	8400	10000	1.65
BTW 80 CTN9/SP		125	54	47.5	140	6.55	5600	6700	1.95